



BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



PWX RANGE PRESSURE WASHERS



BELLE
LIGHT
CONSTRUCTION
EQUIPMENT

FEATURES & BENEFITS

- Robust, compact full Engine & Pump protection frame complete with hose storage facility as standard.
- Professional Honda petrol and Yanmar Diesel engine options with recoil start.
- Detergent / chemical feed-line complete with strainer filter.
- Single point lift to minimize manual handling risk.
- Folding and lockable transport handle.
- Puncture-proof integrated wheels.
- Accessible service points.
- Inlet-line strainer for added pump protection.
- Low engine oil cut-off.
- High quality, heavy-duty triple piston pump.
- Professional two-wire, 10m braided hose, complete with quick-screw adapters and swivel couplings.
- Thermal pump protection.
- Lance holder integrated into protection frame.
- Lance comes complete with safety trigger lock.
- Specifically designed for hire and rental markets.
- Customer colour options available.
- Optional hose reel available.



SINGLE POINT LIFT



FOLDING, LOCKABLE TRANSPORT HANDLE



HOSE REEL OPTION



HIGH QUALITY TRIPLE PISTON PUMP WITH THERMAL PROTECTION & INLET STRAINER

TECHNICAL SPECIFICATIONS

Model	PWX 08/180	PWX 13/230	PWX 15/250	PWX 15/250D
Part No.	P0818015	P1323015	P1525015	P152501DS
Part No. (c/w Hose Reel)	P081801RS	P132301RS	P152501RS	P152501DRS
Engine	Honda GX200	Honda GX270	Honda GX390	Yanmar L100
Engine Power (Hp-kW)	5.8 - 4.3	8.5 - 6.3	11.7 - 8.7	8.9 - 6.6
Electric Start	No	No	No	Yes
Water Flow (lpm)	8	13	15	15
Max. Water Pressure (bar-psi)	180-2600	230-3300	250-3600	250-3600
Fuel Tank Capacity (Ltrs)	3.1	5.3	6.1	5.4
Gearbox Driven Pump	No	No	Yes	Yes
Width (mm)	583	624	624	624
Height (mm)	612	618	732	732
Length (mm)	700	778	778	778
Weight (kg)	57	71	96	136
Noise Level (dB(A))	108	109	109	110



**BELLE
LIGHT
CONSTRUCTION
EQUIPMENT**

ALTRAD BELLE
Sheen, Nr. Buxton, Derbyshire, SK17 0EU, GB
Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 - Email: sales@altrad-belle.com
www.Altrad-Belle.com
www.ALTRAD-Belle247.com